

AD-55-VS-100-092



Evaporative cooler with top air outlet


	DESCRIPTION	UNITS	DATA
AIR FLOW	Air flow	m ³ /h	50.869
	Available static pressure	Pa	104
ENGINE	Rated power	kW	9,20
	Nominal consumption	A	17,8 A (400V/50Hz)
	Speeds	Units	1 speed / frequency inverter
	Tension	V/Phases/Hz	400/III/50-60 Hz
	Regulation type	-	1 speed / frequency inverter
FAN	Typo	-	Centrifugal with forward blades
	Diameter	mm	-
	Speed	Rpm	360 (PM-112 PV-450)
	Drive belts	Units	3 x QUADPOWER XPA 2430
PUMP	Model	-	WILO TM 32/7
	Power / Nominal consumption	-	250W / 1,50 A
	Flow (2m height)	l/m	115
	Tension	V/Phases/Hz	230/I/50
	Level switch	-	Yes
COOLING	Panel type	-	5090
	Dimensions	mm	1500x600x100
	Quantity	Units	12
	Total panel surface	m ²	10,80
	Panel air speed	m/s	1,30
	Panel efficiency	%	89,0
	Temperature impulsión (40°C – 30% HR)	°C	26,7 °C
Pre filter G4	-	Optional	
SOUND LEVEL	Sound level	dB (A) 3m	73
CONNECTIONS	Inlet solenoid valve	Inches	½"
	Water evacuation	Inches	1 ¼"
	Overflow	Inches	1"
CLEANING SYSTEM	Automatic emptying	-	Yes
	UV lamp	-	Optional
CONTROL TYPE	Electric panel 1 speed	-	Optional
	Electric panel with frequency inverter	-	Optional
DIMENSIONS	Overall dimensions	Width/Length/Height	2189x2189x1991mm
	Mouthpiece connexion dimensions	Width/length	935x890mm
	Empty weight / operating	Kg	575 / 770
CERTIFICATES			CE

AD-55-VS-100-092

Evaporative cooler with top air outlet



Prestaciones AD-55 (9,2 kW)



Standard design details

- Water tray made of polyamide
- Corner and central posts in stainless steel AISI-304
- Top roof, side outlet and inlet grilles in galvanised polyester powder coated (INOX version in AISI-304)
- Cooling panels type 5090 of 100mm thick
- Centrifugal fan unit with forward blades and hot-dip galvanised frame
- Automatic draining system patented by MET MANN
- SCHAEFFLER DUROTECT corrosion-resistant bearings with protective caps
- Maintenance-free QUAD-POWER4 power transmission belts from GATES
- WILO IP 68 water pump with level switch
- High efficiency electric motor IE3 IP 55
- Normally closed inlet solenoid valve
- Half-turn opening system for access to the inside of the unit
- Base stand with legs supplied as standard for ease of transport and installation

Custom manufacturing

- Air filtration to comply with BRC food standards
- Customized air flows and pressures
- ATEX motors for explosive environments, etc...




AD-55-VS-100-092

Evaporative cooler with top air outlet



Overall dimensions




AD-55-VS-100-092

Evaporative cooler with top air outlet



Surface installation with diffuser




POSITION	DESCRIPTION	UNITS	STANDARD	INOX
01	Evaporative cooler AD-55-VS-100-092	1	15015531092S	15015531092I
02	Electric panel 1 speed / frequency inverter	1	0415CET092400	0415CF092400
03	Flexible joint JE-850 (935x890)	1	1805AV9389	
04	Straight section TR-850 (935x890x1000)	1	1805TR55	
05	Curved section 90° TC-850 (935x890)	1	1805TC55	
06	Coupling (935x890/900x900)	1	180590907976	
07	3-way air diffuser DCH-3-55	1	0323150155301	
-	Pre filter PG4-40	12	04150140G412	04150140G412I
-	UV WATER treatment	1	031501102020M	
-	Protective case FU-55-VS	1	030215020551W	

AD-55-VS-100-092

Evaporative cooler with top air outlet



Surface installation with impulsion nozzles



POSITION	DESCRIPTION	UNITS	STANDARD	INOX
01	Evaporative cooler AD-55-VS-100-092	1	15015531092S	15015531092I
02	Electric panel 1 speed / frequency inverter	1	0415CET092400	0415CF092400
03	Flexible joint JE-850 (935x890)	1	1805AV9389	
04	Straight section TR-850 (935x890x1000)	1	1805TR55	
05	Curved section 90° TC-850 (935x890)	1	1805TC55	
06	Coupling (935x890/900x900)	1	180590907976	
07	High induction nozzles CI-300	1	04150PAKCONO	
-	Pre filter PG4-40	12	04150140G412	04150140G412I
-	UV WATER treatment	1	031501102020M	
-	Protective case FU-55-VS	1	030215020551W	